



## LUMINAIRE DATA-SHEET

**Model** APOLLO IP PLUS  
**Type** Recessed Spotlight Pinhole Series



### LUMINAIRE IMAGE, DRAWING



### LUMINAIRE GENERAL SPECIFICATION

<b>LAMP TYPE</b>	LED COB
<b>CRI</b>	>90
<b>MacAdam STEP</b>	≤3
<b>INPUT VOLTAGE</b>	AC 220-240V / 50-60 Hz.
<b>MATERIAL</b>	Aluminum Housing White finish
<b>CUT-OFF ANGLE</b>	40°
<b>DIAMETER</b>	Ø 88mm
<b>CUT-OUT</b>	Ø 75mm
<b>DEPTH</b>	D 108mm
<b>IP RATING</b>	IP 54
<b>DRIVER TYPE</b>	Remote in False Ceiling
<b>LUMINOUS FLUX</b>	12W 780 lm (at 3000K & 24°)
	15W 950 lm
<b>OPERATING TEMP</b>	-20°C ... +50°C
<b>LIFESPAN</b>	>50,000 working hours



### LUMINAIRE DETAILED SPECIFICATION & ARTICLE NUMBER

Model	Trimless / With Trim	Adjustability	Power [W]	CCT [Kelvin]	Optics [°]	Control
Apollo IP Plus	1... with Trim	F... Fix	12	2... 2700	15	ND... Non Dim
			15	3... 3000	24	DA... Dali
				4... 4000	38	10... 0-10V

### ARTICLE NUMBER

ApolloIPPlus	-	1	F			
--------------	---	---	---	--	--	--

Model Code      Trim Code      Adjust Code      Power      CCT      Optics      Control Code

**Example:**      **ApolloIPPlus-1F9324ND**      With Trim, Fix, 9W, 3000K, 24°, Non Dim

**Other versions on request.** Please contact us for more information as well as for IES files.