THE DOWNLIGHT FACTORY
AUSTRIAN LIGHTING SOLUTIONS

LUMINAIRE DATA-SHEET

Model **EROS PLUS**
Type Recessed Spotlight Antiglare Series

LUMINAIRE IMAGE, DRAWING

Fixed Versions

Drawings With Trim / Trimless









LUMINAIRE GENERAL SPECIFICATION

LAMP TYPE	LED COB	
CRI	>90	
MacAdam STEP	≤3	
INPUT VOLTAGE	AC 220-240V / 50-60 Hz.	
MATERIAL	Aluminum Housing Metallized Reflector Trim version in white	
CUT-OFF ANGLE	38°	
DIAMETER	Ø 85/71mm (trim/trimless)	
CUT-OUT	Ø 76mm	
DEPTH	D 112mm	
IP RATING	IP 20	
DRIVER TYPE	Remote in False Ceiling	
ADJUSTABILITY (in case of adj. version)	25° tiltable 355° rotatable	
LUMINOUS FLUX *(at 3000K & 24°)*	12W 15W	1043 lm 1296 lm
OPERATING TEMP	-20°C … +50°C	
LIFESPAN	>50,000 working hours	

LUMINAIRE DETAILED SPECIFICATION & ARTICLE NUMBER

Model	Trimless / With Trim	Adjustability	Power [W]	CCT [Kelvin]	Reflector Color	Optics [°]	Control
Eros Plus	0… Trimless 1… with Trim	A… Adjustable F… Fix	12 15	2… 2700 3… 3000 4… 4000	G… Glossy Silver M… Matt Silver T… Titanium	15 24 38	ND… Non Dim DA… Dali 10… 0-10V

ARTICLE NUMBER

ErosPlus	-							
Model Code		Trim Code	Adjust Code	Power	CCT	Reflector Code	Optics	Control Code

Example: **ErosPlus-1A123G24ND** With Trim, Adjustable, 12W, 3000K, Glossy Silver Reflector, 24°, Non Dim

OPTIONAL ACCESSORIES

PRODUCT NAME	IMAGES
Honeycomb Louvre	
Beam Soft Lens	

REFLECTOR COLORS

Please contact us for more information as well as for IES files.